

## Verti-Quake® 2516

The Verti-Quake® de-compacts the soil profile with powered offset blades. The blades' rotary action, combined with the forward speed created a wave motion to move the ground laterally and de-compact consistently from the top of the soil to full working depth with little playing surface disruption.



### Specifications

SKU	115.251.600
Operation	Tractor Mounted
Working width (m)	1.6
Working width (inch)	63
Max. Working depth (mm)	250
Max. Working depth (inch)	9.8
Max. Working speed (km h)	1.5
Weight (kg)	575
Weight (lbs)	1355
Number of knives (blades)	18
Distance between knife discs (mm)	260
Distance between knife discs (inch)	10.2
Standard knife thickness (mm)	12
Min. Tractor HP required	30-45
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	750
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	1653
Max. capacity ( m <sup>2</sup> hr)	2400
Max. capacity (ft <sup>2</sup> hr)	25833
Three-point hitch	3-point CAT 1-2
Rpm Max.	540
Gearbox oil	SAE 90
Lubricant	EP 2

### Distributed by:



[www.centaur-asiapacific.com](http://www.centaur-asiapacific.com)  
[info@centaur-asiapacific.com](mailto:info@centaur-asiapacific.com)

\*Hong Kong, Macau, Malaysia (Johor).